# Suntan<sub>®</sub> Su<sub>®</sub>

# KBPC50005W THRU KBPC5010W

## SINGLE-PHASE BRIDGE RECTIFIER

REVERSE VOLTAGE 50 to 1000 Volts FORWARD CURRENT 50.0 Ampere

### FEATURES

- ♦ High forward surge current capability
- ◆Low thermal resistance
- $\bullet$  High isolation voltage from case to lugs
- ♦ High temperature soldering guaranteed:

260°C /10 second, at 5 lbs. (2.3kg) tension

#### Mechanical Data

- ♦Case: Metal case
- ◆ Terminal: Plated 0.25" (6.35mm) lug
- Polarity: Polarity symbols marked on case
- ♦ Mounting: Thru hole for #10 screw, 20 in,- lbs. Torqute

Max

♦ Weight: 1.02 ounce, 29 gram

#### Hole for No.8 screw 193'(4.9)dian 1.114(28.3) 1.114(28

**Dimensions in inches and (millimeters)** 

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

### Rating at 25°C ambient temperature unless otherwise specified.

#### Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%

PARAMETER		SYMBOL	KBPC 50005W	KBPC 5001W	KBPC 5002W	KBPC 5004W	KBPC 5006W	KBPC 5008W	KBPC 5010W	UNIT
Maximum Repetitive Peak Reverse Voltage		V <sub>RRM</sub>	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage		V <sub>RRM</sub>	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage		V <sub>DC</sub>	50	100	200	400	600	800	1000	Volts
Maximum Average Forward		I <sub>(AV)</sub>	50							Amps
Rectified Output Current, at TC=55°C (Note1,2)										
Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)		Ifsm	400							Amps
Rating for Fusing(t<8.3ms)		$I^2t$	664							A <sup>2</sup> S
Maximum Instantaneous Forward Voltage at 7.5A		$V_{\rm F}$	1.1							Volts
Maximum DC Reverse Current at	Ta=25°C	т	5.0							μAmps
rated DC blocking voltage	Ta=150°C	- Ir	1.0							mAmps
Isolation Voltage from case to lugs		V <sub>ISO</sub>	2500							V <sub>AC</sub>
Typical Thermal Resistance (Note 1,2)		Røjc	2.0							°C/W
Operating Temperature Range		T <sub>J</sub>	-65 to +150							°C
Storage Temperature Range		Tstg	-65 to +150							°C

Note: 1. Unit mounted on 5"×4"×3" thick (12.8mm×10.2mm×7.3mm) Al. plate.

2. Bolt down on heat-sink with silicone thermal compound between bridge and mounting surface for maximum heat transfer efficiency with #10 screw.

# KBPC-W

# Suntan<sub>®</sub>Su<sub>®</sub>

# KBPC50005W THRU KBPC5010W

### SINGLE-PHASE BRIDGE RECTIFIER

REVERSE VOLTAGE 50 to 1000 Volts FORWARD CURRENT 50.0 Ampere

### RATING AND CHARACTERISTIC CURVES KBPC50005W THRU KBPC5010W




FIG.3-TYPICAL FORWARD CHARACTERISTICS PER BRIDGE LEMENT






FIG.5-MAXIMUM POWER DISSIPATION




Note: Specifications are subject to change without notice. For more detail and update, please visit our website.



NUMBER OF CYCLES AT 60 Hz

FIG.4-TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT



REVERSE VOLTAGE,(%)