

MOTOR CAPACITOR-CBB60

Suntan®

ELECTRICAL APPARATUE USE METALLIZED FILM WITH PRECISELY QUALITY CONTROL

FEATURES

- Low D.F. (dissipation factor), good self-healing character
- High I.R. (insulation resistance)
- High safety & high reliability
- Anti-Striking current, strong over-carrier capacity


TS11




S P E C I F I C A T I O N S

OPERATING CONDITION	-40°C ~ +85°C	
CAPACITANCE RANGE	1uF~100uF(TS11-10~21)	
CAPACITANCE TOLERANCE	J(±5%)、K(±10%)	
RATED VOLTAGE	250V 450V (AC)	
WITHSTAND VOLTAGE	Withstand voltage test	
	Test area	Test voltage
	T-T	rated voltage
	T-C	2400VAC(If all shell made of insulating materials, without any test in this project)
		time
		2s
		/
DISSIPATION FACTORY	≤0.004 100Hz (TS11-10~21)	
INSULATION RESISTANCE	≥3000S	


TS11-10




TS11-11




TS11-12




TS11-13




TS11-14




TS11-15




TS11-16




TS11-17




TS11-18




TS11-19 (only for D:30mm)



TS11-20



TS11-21



Please visit our website to get more update data, those data & specification are subject to change without notice.

MOTOR CAPACITOR-CBB60

Suntan®

ELECTRICAL APPARATUE USE METALLIZED FILM WITH PRECISELY QUALITY CONTROL

FEATURES

TS11

- Low D.F. (dissipation factor), good self-healing character
- High I.R. (insulation resistance)
- High safety & high reliability
- Anti-Striking current, strong over-carrier capacity

Dimensions (mm)

CAP	TS11-11				TS11-12				TS11-13				TS11-14			
	250VAC		450VAC		250VAC		450VAC		250VAC		450VAC		250VAC		450VAC	
uF	D	H	D	H	D	H	D	H	D	H	D	H	D	H	D	H
1	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
1.5	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
2	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
2.5	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
3	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
3.5	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
3.75	--	--	--	--	30	50	30	50	30	57	30	57	--	--	--	--
4	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
4.5	30	50	30	60	30	50	30	60	30	57	30	57	30	50	30	60
4.7	30	50	30	60	30	50	30	60	30	57	30	57	--	--	--	--
5	30	50	30	60	30	50	30	60	30	57	35	60	30	50	30	60
6	30	50	30	60	30	50	30	60	30	57	35	60	30	50	30	60
6.3	30	50	30	60	30	50	30	60	30	57	35	60	--	--	--	--
7	30	60	30	60	30	60	30	60	35	60	35	60	30	60	30	60
8	30	60	30	60	30	60	30	60	35	60	35	60	30	60	30	60
9	--	--	--	--	30	60	35	60	35	60	35	60	--	--	--	--
10	30	60	35	60	30	60	35	60	35	60	35	60	30	60	35	60
11	--	--	--	--	30	60	35	60	--	--	--	--	--	--	--	--
12	35	60	35	60	35	60	35	60	35	65	35	60	35	60	35	60
12.5	35	60	35	60	35	60	35	60	35	65	35	60	35	60	35	60
13	35	60	35	60	35	60	35	60	--	--	--	--	35	60	35	60
14	35	60	35	60	35	60	35	70	35	65	35	60	35	60	35	70
15	35	60	35	60	35	60	35	70	35	65	35	60	35	60	35	70
16	35	60	35	70	35	60	35	70	35	65	35	65	35	60	35	70
18	35	60	40	70	35	60	40	70	35	65	40	70	35	60	40	70
20	35	60	40	70	35	60	40	70	35	65	40	70	35	60	40	70
22	40	70	40	70	40	70	40	70	35	65	40	70	40	70	40	70
24	40	70	45	70	40	70	45	70	40	70	40	95	40	70	45	70
25	40	70	45	70	40	70	45	70	40	70	40	95	40	70	45	70
30	40	70	45	93	40	70	45	93	40	70	45	95	40	70	45	93
31.5	--	--	--	--	--	--	--	--	40	70	45	95	--	--	--	--
35	40	70	45	93	40	70	45	93	40	70	45	95	40	70	45	93
40	45	70	50	92	45	70	50	92	45	95	50	106	45	70	50	92
45	45	70	50	92	45	70	50	92	45	95	50	106	45	70	50	92
50	45	93	50	92	45	93	50	92	45	95	50	106	45	93	50	92
55	45	93	50	100	45	93	50	100	45	95	50	106	45	93	50	100
60	45	93	50	100	45	93	50	100	45	95	50	106	45	93	50	100
65	45	93	50	120	45	93	50	120	45	95	50	116	45	93	50	120
70	50	100	50	120	50	92	50	120	50	106	50	116	45	93	50	120
75	50	100	55	117	50	100	55	117	50	106	55	120	50	100	55	117
80	50	100	55	117	50	100	55	117	50	106	55	120	50	100	55	117
85	50	100	60	120	50	100	60	120	50	106	60	120	50	100	60	120
90	50	100	60	120	50	100	60	120	50	106	60	120	50	100	60	120
100	50	100	60	120	50	100	60	120	50	106	60	120	50	100	60	120

Please visit our website to get more update data, those data & specification are subject to change without notice.

MOTOR CAPACITOR-CBB60

Suntan®

ELECTRICAL APPARATUE USE METALLIZED FILM WITH PRECISELY QUALITY CONTROL

FEATURES

TS11

- Low D.F. (dissipation factor), good self-healing character
- High I.R. (insulation resistance)
- High safety & high reliability
- Anti-Striking current, strong over-carrier capacity

Dimensions (mm)

CAP	TS11-15				TS11-16				TS11-17				TS11-18			
	250VAC		450VAC		250VAC		450VAC		250VAC		450VAC		250VAC		450VAC	
uF	D	H	D	H	D	H	D	H	D	H	D	H	D	H	D	H
1	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
1.5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
2	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
2.5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
3	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
3.5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
3.75	30	57	30	57	--	--	--	--	30	57	30	57	30	50	30	50
4	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
4.5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	60
4.7	--	--	--	--	--	--	--	--	--	--	--	--	30	50	30	60
5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	60
5.5	--	--	--	--	--	--	--	--	--	--	--	--	30	50	30	60
6	30	57	35	60	30	57	35	60	30	57	35	60	30	50	30	60
6.3	30	57	35	60	30	57	35	60	30	57	35	60	30	50	30	60
6.5	--	--	--	--	--	--	--	--	--	--	--	--	30	50	30	60
7	35	60	35	60	35	60	35	60	35	60	35	60	30	60	30	60
7.5	--	--	--	--	35	60	35	60	--	--	--	--	--	--	--	--
8	35	60	35	60	35	60	35	60	35	60	35	60	30	60	35	60
9	35	60	35	60	35	60	35	60	--	--	--	--	30	60	35	60
10	35	60	35	60	35	60	35	60	35	60	35	60	30	60	35	60
11	35	60	35	60	--	--	--	--	--	--	--	--	--	--	--	--
12	35	65	35	60	35	65	35	60	35	65	35	60	35	60	35	60
12.5	35	65	35	60	35	65	35	60	35	65	35	60	35	60	35	60
13	--	--	--	--	35	65	35	60	--	--	--	--	--	--	--	--
14	35	65	35	60	35	65	35	60	35	65	35	60	35	60	35	70
15	35	65	35	60	35	65	35	60	35	65	35	60	35	60	35	70
16	35	65	35	65	35	65	35	65	35	65	35	65	35	60	35	70
18	35	65	40	70	35	65	40	70	35	65	40	70	35	60	40	70
20	35	65	40	70	35	65	40	70	35	65	40	70	35	60	40	70
22	35	65	40	70	35	65	40	70	35	65	40	70	40	70	40	70
24	40	70	45	95	40	70	40	95	40	70	40	95	40	70	45	70
25	40	70	45	95	40	70	40	95	40	70	40	95	40	70	45	70
30	40	70	45	95	40	70	45	95	40	70	45	95	40	70	45	93
33	--	--	--	--	--	--	--	--	--	--	--	--	40	70	45	93
35	40	70	45	95	40	70	45	95	40	70	45	95	40	70	45	93
40	45	95	50	106	45	95	50	106	45	95	50	106	45	70	50	92
45	45	95	50	106	45	95	50	106	45	95	50	106	45	70	50	92
50	45	95	50	106	45	95	50	106	45	95	50	106	45	93	50	92
55	45	95	50	106	45	95	50	106	45	95	50	106	45	93	50	100
60	45	95	50	106	45	95	50	106	45	95	50	106	45	93	50	100
65	45	95	50	116	45	95	50	116	45	95	50	116	45	93	50	120
70	50	106	50	116	50	106	50	116	50	106	50	116	50	100	50	120
75	50	106	55	120	50	106	55	120	50	106	55	120	50	100	55	117
80	50	106	55	120	50	106	55	120	50	106	55	120	50	100	55	117
85	50	106	60	120	50	106	60	120	50	106	60	120	50	100	60	120
90	50	106	60	120	50	106	60	120	50	106	60	120	50	100	60	120
100	50	106	60	120	50	106	60	120	50	106	60	120	50	100	60	120

Please visit our website to get more update data, those data & specification are subject to change without notice.

Suntan® Technology Company Limited Website: www.suntan.com.hk Email: info@suntan.com.hk Tel: (852) 8202 8782 Fax: (852) 8208 6246